CT-2 超薄低高度台式隔振平台

Weight: Approximately 30 lbs (16 kg)	
Dimension: 18" W x 20" D x 2.7" H (457mm W x 508mm D x 68.6mm H)	
Approximate payload weight range	
Model	Payload Range
30CT-2	18 – 31 lb. (8.2 – 14 kg.)
60CT-2	42 – 70 lb. (19 – 31.7 kg.)
100CT-2	68 – 104 lb. (31 – 47 kg.)
150CT-2	112 – 158 lb. (51 – 71.5 kg.)
200CT-2	155 – 210 lb. (70.5 – 95.2 kg.)
250CT-2	205 – 252 lb. (93 – 114.3 kg.)
Performance	

- Performance
- · Horizontal frequencies are weight dependent.
- Horizontal frequency of ~1.5 Hz is achieved at or near the upper limits of the payload range.
- At the lower payload weights the horizontal frequency will increase.
- Vertical frequency is tunable to 0.5 Hz throughout the payload range.



The Compact Tabletop (CT-2) uses Minus K's patented breakthrough technology allowing for the best performance on the market in just a 2.7-inch-tall isolation platform. This unit is an upgrade from Minus K's CT-1 and offers better horizontal performance with additional payload ranges for heavier instruments.

This completely passive mechanical isolator offers 10 -100 times better performance than a full-size air table. It does this without any air or electricity!

This vibration isolation platform is extremely easy to use and offers our signature 0.5 Hz vertical natural frequency and \sim 1.5 Hz horizontal natural frequency. There are only two adjustments. The CT-2 is ideal for all types of benchtop microscopes.

This is the thinnest, most portable and most user-friendly isolator ever offered that is capable of delivering this performance.

The vertical curve below demonstrates the vertical 1/2 Hz performance of the CT-2. Horizontally, the CT-2 offers natural frequencies as low as 1.5 Hz, much better than typical air tables.

Typical Performance Curves:



